Revision: 07.10.2023



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.10.2023

Version number 11 (replaces version 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ACRY TRAY LIQUIDO
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages PW Widespread use by professional workers
- · Application of the substance / the mixture Material for dental use
- · Uses advised against Any use other than those identified is not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dental Manufacturing S.p.a.

Via Cà Mignola Nuova, 1699

45021 - Badia Polesine (RO) - Italy

Tel. +39 0425 51628 - Fax +39 0425 590156

- · Further information obtainable from: info@ruthinium.it
- · 1.4 Emergency telephone number:

Dental Manufacturing S.p.a. - Tel. +39 0425 51628 (Office Hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate ethyl methacrylate

1,4-Butanediol dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

(Contd. of page 1)

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

methyl methacrylate
ethyl methacrylate
1.4 Butanadial dimetha

1,4-Butanediol dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28- xxxx	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	80-100%
CAS: 97-63-2 EINECS: 202-597-5 Index number: 607-071-00-2	ethyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-15%
CAS: 2082-81-7 EINECS: 218-218-1 Index number: 607-134-00-4	1,4-Butanediol dimethacrylate Skin Sens. 1, H317; STOT SE 3, H335	2-5%

(Contd. on page 3)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Rescue workers must wear the protective equipment described in section 8.2 of this safety data sheet.

· IF INHALATED:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If ingested do not induce vomiting, seek medical assistance showing the safety data sheet or the hazard label

- · **4.2 Most important symptoms and effects, both acute and delayed** *Irritation of eyes, skin and respiratory tract.*
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment:

Use respiratory protection

Wear personal protective clothing.

See Section 8 for information on personal protection equipment.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

You should follow the usual precautions for handling chemical products Ensure good ventilation/exhaustion at the workplace.

Avoid contact with eyes and skin.

(Contd. on page 4)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 80-62-6 methyl methacrylate (80-100%)

OEL Short-term value: 100 ppm Long-term value: 50 ppm IOELV, Sens

· DNELs

CAS: 80-62-6 methyl methacrylate

O/10. 00 C	2 o meany meanaory ac	
Dermal	Long term, local effect	1.5 mg/kg (general population)
		1.5 mg/kg (professional workers)
	Long term, systemic effect	13.67 mg/kg (professional workers)
	Long term, systemic effect	8.2 mg/kg bw/day (general population)
Inhalative	Long term, local effect	105 mg/m3 (general population)
		210 mg/m3 (professional workers)
	Long term, systemic effect	74.3 mg/m3 (general population)
		210 mg/m3 (professional workers)

· PNECs

CAS: 80-62-6 methyl methacrylate

PNEC 5.74 mg/kg (fresh water sediments)

PNEC 0.94 mg/l (freshwater) 0.094 mg/l (marine water)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Rubber gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Breakthrough time:> = 480 min - Material thickness:> = 0.7 mm Breakthrough time:> = 60 min - Material thickness:> = 0.5 mm Breakthrough time:> = 30 min - Material thickness:> = 0.2 mm

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Odour threshold:

Liquid
Colourless

Characteristic
Not determined.

Melting point/freezing point: -48.2 °C

· Boiling point or initial boiling point and

boiling range 100.3 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

 ⋅ Lower:
 2.1 Vol %

 ⋅ Upper:
 12.5 Vol %

 ⋅ Flash point:
 10 °C

 ⋅ Auto-ignition temperature:
 430 °C

· **pH** Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 0.63 mPas

· Solubility

• water at 20 °C: 15.9 g/l

· Partition coefficient n-octanol/water (log

value) 1.38 log POW Vapour pressure at 20 °C: 38.7 hPa

Density and/or relative density

Density at ù °C: 0.94 g/cm³

(Contd. on page 6)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

	(Contd. of page
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
Form:	Liquid
Important information on protection of hea	alth .
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Change in condition	,
· Evaporation rate	Not determined.
Information with regard to physical hazard	1
classes	
· Explosives	Void
· Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Highly flammable, vapours may form explosive mixture with air
- · 10.2 Chemical stability The product is stable under normal conditions of use and storage
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

· Organic peroxides

· Corrosive to metals

· Desensitised explosives

If heated, exposed to air, sun or the addition of free radical initiators, it may polymerise exortem

Void

Void

Void

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Avoid contact with acids and oxidants.
- · 10.6 Hazardous decomposition products:

When heated or in case of fire can release gases and vapors which are dangerous to health.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 80-62-6 methyl methacrylate

Oral LD50 7,872 mg/kg (rat)

(Contd. on page 7)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

		(Contd. of page 6)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	33 mg/l (mouse)	
		29.8 mg/l (rat)	
CAS: 97-6	CAS: 97-63-2 ethyl methacrylate		
Oral	LD50	14,800 mg/kg (rat)	
CAS: 208	CAS: 2082-81-7 1,4-Butanediol dimethacrylate		
Oral	LD50	>10,000 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rabbit)	

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

	12.1 Toxioney		
· Aquati	· Aquatic toxicity:		
CAS: 8	CAS: 80-62-6 methyl methacrylate		
CL50	>79 mg/l (fish) (Esposizione 96 h)		
EC50	50 69 mg/kg (daphnia)		
EC50	>110 mg/l (algae) (Esposizione 72 h)		
	69 mg/l (daphnia) (Esposizione 48 h)		
NOEC	NOEC 37 mg/l (daphnia)		
	9.4 mg/l (fish)		
CAS: 2	082-81-7 1,4-Butanediol dimethacrylate		
CL50	32.5 mg/l (fish)		
EC50	EC50 7.51 mg/l (crustaceans)		
NOEC	7.51 mg/l (crustaceans)		
	the trace for the trace tells		

- 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential Non significant accumulation in organisms
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 8)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

(Contd. of page 7)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Do not discard the product or its packaging. Do not empty into drains. Recycle the product. When recycling is not possible, dispose through an authorized company in compliance with the local or national regulations. The assignment of the waste code is the user's responsibility, after determining the properties of the waste and the process generating it and after discussing it with the authorities responsible for disposal.

- · Uncleaned packaging:
- Recommendation:

Empty the containers before disposal. Do not reuse the emptied containers. Send the empty containers to recycling or to an authorized company in compliance with local and national regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR	1247 METHYL METHACRYLATE MONOMER,
IMDG, IATA	STABILIZED solution METHYL METHACRYLATE MONOMER, STABILIZED solution
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids.
	3
14.4 Packing group ADR, IMDG, IATA	II .
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D B
Stowage Category	SW2 Clear of living quarters.

(Contd. on page 9)

Printing date 07.10.2023 Version number 11 (replaces version 10) Revision: 07.10.2023

Trade name: ACRY TRAY LIQUIDO

	(Contd. of page 8
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport categoryTunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety data sheet prepared in accordance with Regulation 1907/2006/EC Article 31, Regulation (EU) No 878/2020 as subsequent amendments.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Classification according to Regulation (EC) No 1272/2008

As required by Regulation 1272/2008/CE art. 9, the classification of this compound is based on the calculation method taken from the data of the single substances therein and from the experimental data of this compound where available (viewable in sections 9, 11 and 12 in this document).

(Contd. on page 10)

Printing date 07.10.2023 Version number 11 (replaces version 10)

Trade name: ACRY TRAY LIQUIDO

(Contd. of page 9)

Revision: 07.10.2023

Procedure used for the classification of the mixture

Flam. Liq. 2, H225 - According to experimental data

Skin Irrit. 2, H315 - Calculation method

Skin Sens 1 / 1A / 1B, H317 -Calculation method

Eye Irrit. 2, H319 - Calculation method

STOT SE 3, H335 - Calculation method

· Date of previous version: 31.01.2018

· Version number of previous version: 10

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

·IE